



| WI1210-1R0M | 1.0 | ±20% |  | 1M | 1M |  |  |  |  |
|-------------|-----|------|--|----|----|--|--|--|--|
| WI1210-1R2M | 1.2 | ±20% |  | 1M | 1M |  |  |  |  |
| WI1210-1R5M | 1.5 | ±20% |  | 1M | 1M |  |  |  |  |
| WI1210-1R8M | 1.8 | ±20% |  | 1M | 1M |  |  |  |  |
| WI1210-2R2M | 2.2 | ±20% |  | 1M | 1M |  |  |  |  |
| WI1210-2R7M | 2.7 | ±20% |  | 1M | 1M |  |  |  |  |
| WI1210-3R3M | 3.3 | ±20% |  | 1M | 1M |  |  |  |  |
| WI1210-3R9M | 3.9 | ±20% |  | 1M | 1M |  |  |  |  |
| WI1210-4R7M | 4.7 | ±20% |  | 1M | 1M |  |  |  |  |
| WI1210-5R6M | 5.6 | ±20% |  | 1M | 1M |  |  |  |  |
| WI1210-6R8M | 6.8 | ±20% |  | 1M | 1M |  |  |  |  |
| WI1210-100K | 10  | ±10% |  | 1M | 1M |  |  |  |  |
| WI1210-120K | 12  | ±10% |  | 1M | 1M |  |  |  |  |
| WI1210-150K | 15  | ±10% |  | 1M | 1M |  |  |  |  |
| WI1210-180K | 18  | ±10% |  | 1M | 1M |  |  |  |  |
| WI1210-220K | 22  | ±10% |  | 1M | 1M |  |  |  |  |
| WI1210-330K | 33  | ±10% |  | 1M | 1M |  |  |  |  |



|             |     |      |    |    |      |     |      | $\Delta$ °C | $\Delta$ °C |
|-------------|-----|------|----|----|------|-----|------|-------------|-------------|
|             |     |      |    |    |      |     |      |             |             |
| W11210-390K | 39  | ±10% | 40 | 1M | 1M   | 11  | 2.00 | 115         | 152         |
| W11210-470K | 47  | ±10% | 40 | 1M | 1M   | 11  | 3.00 | 110         | 146         |
| W11210-680K | 68  | ±10% | 35 | 1M | 1M   | 9   | 3.80 | 96          | 130         |
| W11210-820K | 82  | ±10% | 35 | 1M | 1M   | 8.5 | 5.60 | 85          | 105         |
| W11210-101K | 100 | ±10% | 40 | 1M | 796K | 8   | 6.50 | 80          | 100         |
| W11210-121K | 120 | ±10% | 40 | 1M | 796K | 7.5 | 7.00 | 75          | 95          |
| W11210-151K | 150 | ±10% | 40 | 1M | 796K | 7   | 9.20 | 70          | 86          |
| W11210-181K | 180 | ±10% | 40 | 1M | 796K | 6   | 10.2 | 65          | 80          |
| W11210-221K | 220 | ±10% | 40 | 1M | 796K | 5.5 | 11.8 | 65          | 75          |
| W11210-271K | 270 | ±10% | 40 | 1M | 796K | 5   | 14.8 | 60          | 70          |
| W11210-331K | 330 | ±10% | 40 | 1M | 796K | 5   | 16.5 | 55          | 65          |
| W11210-391K | 390 | ±10% | 46 | 1M | 796K | 5   | 22.0 | 50          | 60          |
| W11210-471K | 470 | ±10% | 46 | 1K | 796K | 5   | 25.0 | 45          | 55          |
| W11210-561K | 560 | ±10% | 46 | 1K | 796K | 5   | 28.0 | 40          | 48          |

Operating temperature: -40 °C to +125 °C

